

DATASHEET

303575

Arendo Induction Plate

TECHNICAL INFORMATION



BASIC INFORMATION

Dimensions (H x W x L)	6.5 x 28 x 35 cm
Weight	2.52kg
Cable length	1.5m
Induction coil Ø	150 mm
Colour	Black
Connector type	Euro plug type CEE 7/17
Scope of delivery	• Arendo Induction Plate • User Manual

DETAILED DESCRIPTION

Mains voltage	220-240 V AC, 50/60 Hz
Power consumption	200 – 2000 W
Performance levels	10 (200 W, 400 W, 600 W, 800 W, 1000 W, 1200 W, 1400 W, 1600 W, 1800 W, 2000 W)
Temperature steps	60°C, 80°C, 100°C, 120°C, 140°C, 160°C, 170°C, 180°C, 190°C, 200°C
Timer	0-180 min. adjustable in 1 minute steps
Stand-by consumption	0.6 W
Diameter for Suitable cooking utensils	10 - 26 cm; optimal: 15 - 20 cm
Noise level (fan)	49 dBA
Features & Benefits	- Sensor touch control panel - Operating control lamps (LED red) - Automatic pot detection - Overheating protection - automatic disconnection - Key lock - Anti-slip feet - Cooking pot detection for induction capability - Automatic switch-off after 1 minute - Beep/signal tone - Red LED display

GS Mark	✓
---------	---

DATENBLATT

303575

Arendo Induktionsplatte

TECHNISCHE INFORMATIONEN

BASIS-INFORMATIONEN

Abmessungen (H x B x L)	6,5 x 28 x 35 cm
Gewicht	2,52kg
Kabellänge	1,5m
Induktionsspule Ø	150 mm
Farbe	Schwarz
Steckertyp	Eurostecker Typ CEE 7/17
Lieferumfang	• Arendo Induktionsplatte • Bedienungsanleitung

DETAILLIERTE SPEZIFIKATIONEN

Netzspannung	220-240 V AC, 50/60 Hz
Leistungsaufnahme	200 – 2000 W
Leistungsstufen	10 (200 W, 400 W, 600 W, 800 W, 1000 W, 1200 W, 1400 W, 1600 W, 1800 W, 2000 W)
Temperaturstufen	60°C, 80°C, 100°C, 120°C, 140°C, 160°C, 170°C, 180°C, 190°C, 200°C
Timer	0-180 min. in 1 Minuten-Schritten einstellbar
Stand-By-Verbrauch	0,6 W
Durchmesser für geeignetes Kochgeschirr	10 - 26 cm; optimal: 15 - 20 cm
Geräuschpegel (Lüfter)	49 dBA
Eigenschaften	• Sensor-Touch-Bedienfeld • Betriebskontrollleuchten (LED rot) • Automatische Topferkennung • Überhitzungsschutz • automatische Abschaltung • Schlüsselsperre • Anti-Rutschfüße • Kochtopferkennung für Induktionsfähigkeit • automatische Abschaltung nach 1 Minute • Piepton/Signalton • Rote LED-Anzeige

GS-Siegel	✓
-----------	---

