



## DATASHEET

304588

Arendo Hand Mixer Misca

### TECHNICAL INFORMATION

#### BASIC INFORMATION

|                     |   |
|---------------------|---|
| <b>Dimensions</b>   | (length) 186 x (width) 84 x (height) 155 mm |
| <b>Weight</b>       | 844 g incl. power cable                     |
| <b>Cable length</b> | 1.1 m                                       |
| <b>Material</b>     | Chrome elements / ABS                       |
| <b>Colour</b>       | Grey  |

|                          |  |
|--------------------------|--|
| <b>Scope of delivery</b> | <ul style="list-style-type: none"> <li>• Arendo Hand Mixer Misca</li> <li>• 2 x whisks and 2 x dough hooks</li> <li>• User manual</li> </ul> |
|--------------------------|--|

#### DETAILED DESCRIPTION

|                             |                       |
|-----------------------------|-----------------------|
| <b>Power Supply</b>         | AC 220-240 V 50-60 Hz |
| <b>Power consumption</b>    | Max. 400 W            |
| <b>Operating noise</b>      | max. 70 dBA           |
| <b>Stand-by consumption</b> | 0.05 W                |
| <b>Protection class</b>     | II                    |

|                 |   |
|-----------------|---|
| <b>Features</b> | <ul style="list-style-type: none"> <li>- Engine class 155</li> <li>- Optimum power regulation</li> <li>- Turbo button for full power at the push of a button</li> <li>- Ergonomically shaped housing</li> <li>- Hook release</li> <li>- Thermal fuse</li> <li>- Incl. 2x whisks (whisk) and 2x kneading hooks made of stainless steel</li> <li>- Power cable feed can be swivelled 90° in the housing</li> <li>- With overheating protection</li> </ul> |
|-----------------|---|

**DATENBLATT**
**304588**

Arendo Handmixer Misca

**TECHNISCHE INFORMATIONEN**
**BASIS-INFORMATIONEN**
**Abmessungen** (Länge) 186 x (Breite) 84 x (Höhe) 155 mm

**Gewicht** 844 g inkl. Stromkabel

**Netz-Kabellänge** 1,1 m

**Material** Chromelemente / ABS

**Farbe** Grau

**Lieferumfang**

- Arendo Handmixer Misca
- 2 x Schneebesens und 2 x Knethaken
- Bedienungsanleitung

**DETAILIERTE SPEZIFIKATIONEN**
**Spannungsversorgung** AC 220-240 V 50-60 Hz

**Leistungsaufnahme** Max. 400 W

**Betriebsgeräusch** max. 70 dBA

**Stand-By-Verbrauch** 0,05 W

**Schutzklasse** II

**Eigenschaften**

- Motorklasse 155
- optimale Leistungsregulierung
- Turbotaste für volle Leistung auf Knopfdruck
- Ergonomisch geformtes Gehäuse
- Hakenverriegelung
- Thermosicherung
- Inkl. 2x Quirle (Schneebesens) und 2x Knethacken aus Edelstahl
- Stromkabelzuführung im Gehäuse um 90° schwenkbar
- mit Überhitzungsschutz

