



DATASHEET

303759

Arendo Stainless Steel Kettle With Temperature Settings

TECHNICAL INFORMATION

BASIC INFORMATION

Dimensions	Height: 26 cm Width: 22 cm Length: 17 cm
Weight (kettle) Weight (basis)	• 1072 g • 224 g
Material	• Double-walled insulated • Food safe SUS 304 stainless steel
Colour	Black
Scope of delivery	• Arendo Stainless Steel Kettle With Temperature Settings • User Manual

DETAILED DESCRIPTION

Capacity	Max. 1.5 l
Socket Controller	Strix
Power Supply	220-240V AC, 50 Hz
Power Consumption	2000 W
Cable Length	Aprox. 72 cm
Plug Type	Type F CEE 7/7
Button Function	• Temperature settings • Keep warm function • On/Off switch
Temperature Settings	40° C, 80° C, 90° C, 100° C
Standby Consumption	<0.65 W
Protection	Dry-running protection, Overheating protection, Automatic switch-off, Double-walled insulated
Features	<ul style="list-style-type: none"> • Keep warm function (30min) • with lateral Body-LED-Display (white) • Exact maintenance of the target temperature by intermediate measurements of the temperature sensor • Litre scale on the inside • Concealed heating element for energy-efficient rapid heating • Acoustic signal (indicates operation of the appliance + end of boiling) • Easy to read 1,5l water level indicator • Strix controller, 360° base, with rewind holder for the cable • Automatic and manual switch-off • Anti-slip feet for stable standing on almost any surface
GS Mark	✓
BPA free	✓





DATENBLATT

304895

Arendo Edelstahl-Wasserkocher mit Temperatureinstellung

TECHNISCHE INFORMATIONEN

BASIS-INFORMATIONEN

Abmessungen	Höhe: 26 cm Breite: 22 cm Länge: 17 cm
Gewicht (Wasserkocher) Gewicht (Basiseinheit)	• 1072 g • 224 g
Material	• Doppelwand-Design • Lebensmittelechter SUS 304 Edelstahl
Farbe	Schwarz
Lieferumfang	• Arendo Edelstahl-Wasserkocher mit Temperatureinstellung • Bedienungsanleitung

DETAILLIERTE SPEZIFIKATIONEN

Kapazität	Max. 1,5l
Controller-Typ	Strix
Netzspannung	220-240 V AC, 50 Hz
Stromverbrauch	2000 W
Netzkabel-Länge	Ca. 72 cm
Steckertyp	Typ F CEE 7/7
Tastenbedienung	• Temperatureinstellung • Warmhaltefunktion • AN/AUS-Schalter
Wählbare Temperatureinstellung	40° C, 80° C, 90° C, 100° C
Standby-Verbrauch	<0,65 W
Sicherheitsstandard	Trockengehschutz, Überhitzungsschutz, Automatische Abschaltung, Doppelwandig isoliert
Eigenschaften	<ul style="list-style-type: none"> • Warmhaltefunktion (30min) • mit seitlichem Body-LED-Display (weiß) • Genaues Einhalten der Zieltemperatur durch Zwischenmessungen des Temperaturfühlers • Literskala auf der Innenseite • Verdecktes Heizelement für eine energieeffiziente Schnell-Erhitzung • Akustisches Signal (signalisiert die Bedienung des Gerätes + Beendigung des Aufkochens) • Leicht ablesbare 1,5l Wasser-Füllstandanzeige • Strix-Controller, 360°-Basis, mit Aufwickelhalter für das Kabel • Automatische und manuelle Abschaltung • Anti-Rutsch-Füße für stabilen Stand auf nahezu jeder Oberfläche
GS-Siegel	✓
BPA-frei	✓

