

DATASHEET

305035

Arendo Fryer Professional

TECHNICAL INFORMATION

BASIC INFORMATION

Dimensions (HxWxD)	38 x 21,5 x 25 cm
Weight	2,5 kg
Length (Power cable)	50 cm
Cable diameter	7 mm
Material	Stainless steel applications + ABS
Colour	Black
Scope of delivery	<ul style="list-style-type: none"> • Arendo Fryer • User Manual

DETAILED DESCRIPTION

Power supply	220-240 V AC, 50/60 Hz
Capacity	Max. 3.5 l
Plug type	Type F CEE 7/7
Temperature settings	150-190°C in 5°C steps
Power consumption	2000 W
Timer settings	1-60 minutes
Features	<ul style="list-style-type: none"> - Cold zone technology: the fat stays longer and tastier; sustainable use - Timer dial with times from 0 to 60 minutes - Solid stainless steel housing; components (oil pan, frying basket, handle, lid) can be easily removed and cleaned in the dishwasher (but not the heating coil) - Window in the lid, no splashing of fat and oil - Heat-insulated cool-touch handle - Thermal protection device, can be reactivated - Status LED: red operation indicator - Non-slip feet



DATENBLATT
305035

Arendo Fritteuse Professional

TECHNISCHE INFORMATIONEN
BASIS-INFORMATIONEN

Abmessungen (HxBxT)	38 x 21,5 x 25 cm
Gewicht	2,5 kg
Länge (Stromkabel)	50 cm
Kabeldurchmesser	7 mm
Material	Edelstahl-Applikationen + Kunststoff
Farbe	Schwarz
Lieferumfang	<ul style="list-style-type: none"> • Arendo Fritteuse Professional • Bedienungsanleitung


DETAILLIERTE SPEZIFIKATIONEN

Spannungsversorgung	220-240 V AC, 50/60 Hz
Fassungsvermögen	Max. 3,5 l
Steckertyp	Typ F CEE 7/7
Temperatureinstellung	150-190°C in 5°C Schritten
Leistungsaufnahme	2000 W
Timereinstellung	1-60 Minuten
Eigenschaften	<ul style="list-style-type: none"> • Kaltzontechnik: das Fett bleibt länger haltbar und schmackhaft; nachhaltige Nutzung • Timer-Drehrad mit Zeiten von 0 bis 60 Minuten • Massives Edelstahlgehäuse; Komponenten (Ölschale, Frittierkorb, Griff, Deckel) lassen sich leicht entnehmen und in der Spülmaschine reinigen (nicht aber die Heizspirale) • Sichtfenster im Deckel, kein Spritzen von Fett und Öl • wärmeisolierter Cool-Touch-Griff • Thermische Schutzvorrichtung, reaktivierbar • Status-LED: rote Betriebsanzeige • Rutschfeste Standfüße