



DATASHEET

305567

Arendo GLASS CONTROL Water Kettle

TECHNICAL INFORMATION

BASIC INFORMATION

Dimensions	Height 27.5 cm x width with handle 23 cm x diameter (without handle) 16 cm
Weight (kettle)	• 1024 g
Weight (basis)	• 222 g
Material	Brushed SUS/SAE 304 stainless steel
Colour	Black/silver
Scope of delivery	<ul style="list-style-type: none"> • Arendo GLASS CONTROL Water Kettle • User manual

DETAILED DESCRIPTION

Capacity	Max. 1.7 l
Socket Controller	Strix
Power Supply	220-240 V AC, 50 Hz
Power consumption	1850-2200 W
Cable length	Aprox. 65 cm
Plug	Type F CEE 7/7
Protection	Dry-running protection, overheat protection, automatic shut-off
Features	<ul style="list-style-type: none"> - Selectable temperatures: from 40°C to 100°C in 5°C steps - SET direct selection button for DeepL access to 40°C / 60°C / 80°C / 100°C - White LED display for current temperature and target temperature - Temperature sensor for precise heating - water level indicator on glass body - smooth base, concealed heating element - keep-warm function for 30 min. - Strix base station with stainless steel ring and practical cable winder - 5 buttons („+“ , „-“, SET, KEEP WARM, START) - Automatic and manual switch-off - buzzer; can be switched off except for START sound - automatic display switch-off after 5 min.



DATENBLATT

305567

Arendo GLAS CONTROLL Wasserkocher

TECHNISCHE INFORMATIONEN

BASIS-INFORMATIONEN

Abmessungen	Höhe 27,5 cm x Breite mit Griff 23 cm x Durchmesser (ohne Griff) 16 cm
Gewicht (Wasserkocher)	• 1042 g
Gewicht (Basiseinheit)	• 220 g
Material	Gebürstetes SUS/SAE 304 Edelstahl
Farbe	Schwarz/silber
Lieferumfang	• Arendo GLAS CONTROLL Wasserkocher • Bedienungsanleitung

DETAILLIERTE SPEZIFIKATIONEN

Kapazität	Max. 1,7 l
Controller-Typ	Strix
Netzspannung	220-240 V AC, 50 Hz
Stromverbrauch	1850 W - 2200 W
Kabel-Länge	Ca. 65 cm
Steckertyp	Typ F CEE 7/7
Sicherheitsstandard	Trockengehschutz, Überhitzungsschutz, Automatische Abschaltung,

Features

- wählbare Temperaturen: von 40°C bis 100°C in 5°C-Schritten
- SET-Direktwahltaste für Schnellzugriff auf 40°C / 60°C / 80°C / 100°C
- weiße LED-Anzeige für aktuelle Temperatur und Zieltemperatur
- Temperaturfühler für präzise Erhitzung
- Wasserstandsanzeige am Glaskörper
- glatter Boden, verdecktes Heizelement
- Warmhaltefunktion für 30 min.
- Strix Basisstation mit Edelstahlling und praktischer Kabelaufwicklung
- 5 Tasten („+“, „-“, SET, KEEP WARM, START)
- automatische und manuelle Abschaltung
- Summer; abschaltbar bis auf START-Ton
- automatische Displayabschaltung nach 5 Min.