



## DATASHEET

305681

Arendo Stainless Steel Automatic Drying Machine

### TECHNICAL INFORMATION

#### BASIC INFORMATION

|                          |  |
|--------------------------|--|
| <b>Dimensions</b>        | (H x W x D): 21-27.5 x 26 x 24 cm;<br>single compartment: 3.5 x 25 x 23 cm,<br>surface area 550 cm <sup>2</sup>  |
| <b>Weight</b>            | 1864 g   |
| <b>Material</b>          | Stainless steel + ABS  |
| <b>Colour</b>            | Black/silver   |
| <b>Power cord length</b> | Approx. 90 cm  |
| <b>Plug Type</b>         | Euro plug type F CEE 7/16  |
| <b>Scope of delivery</b> | <ul style="list-style-type: none"> <li>• Arendo Stainless Steel Dehydrator with 5 compartments</li> <li>• Insert mat</li> <li>• User Manual</li> </ul> |

#### DETAILED DESCRIPTION

|                            |  |
|----------------------------|--|
| <b>Mains voltage</b>       | 220-240 V AC, 50/60 Hz   |
| <b>Power consumption</b>   | 220 until 240 W  |
| <b>Temperature level</b>   | Variable temperature setting from 35°C-70°C in 5°C steps   |
| <b>Timer function</b>      | Individually adjustable timer from 1 - 72 hours in 60 min steps  |
| <b>Standby consumption</b> | <0.3 W   |
| <b>Noise level</b>         | 46 dBA   |
| <b>Buttons</b>             | 5 touch buttons (TIME // TEMP // POWER ON/OFF // "+" // "-")   |
| <b>Display type</b>        | LED display for temperature and remaining time indication  |
| <b>Safety standard</b>     | Front flap with lock and large viewing window  |
| <b>Features</b>            | <ul style="list-style-type: none"> <li>- Circulating air function</li> <li>- 5 compartments with a total of 2750 cm<sup>2</sup> drying surface, dishwasher-safe</li> <li>- Two different heights can be set for each compartment</li> <li>- On/off switch easily accessible on the front panel</li> <li>- Compact dimensions, small footprint</li> <li>- Anti-slip feet</li> </ul> |
| <b>Temperature range</b>   | - 5° - 40°C  |



## DATENBLATT

305681

Arendo Edelstahl-Dörrautomat

### TECHNISCHE INFORMATIONEN

#### BASIS-INFORMATIONEN

|                        |  |
|------------------------|--|
| <b>Abmessungen</b>     | (H x B x T): 21-27,5 x 26 x 24 cm;<br>Einzelfach: 3,5 x 25 x 23 cm,<br>Fläche 550 cm <sup>2</sup>  |
| <b>Gewicht</b>         | 1864 g   |
| <b>Material</b>        | Edelstahl + ABS  |
| <b>Farbe</b>           | Schwarz/silber   |
| <b>Netzkabel-Länge</b> | Ca. 90 cm  |
| <b>Steckertyp</b>      | Eurostecker Typ F CEE 7/16   |
| <b>Lieferumfang</b>    | <ul style="list-style-type: none"> <li>• Arendo Edelstahl-Dörrautomat mit 5 Einlegefächern</li> <li>• Einlegematte</li> <li>• Bedienungsanleitung</li> </ul> |

#### DETAILLIERTE SPEZIFIKATIONEN

|                            |   |
|----------------------------|---|
| <b>Netzspannung</b>        | 220-240 V AC, 50/60 Hz  |
| <b>Stromverbrauch</b>      | 220 bis 240 W   |
| <b>Temperaturstufe</b>     | Variable Temperatureinstellung von 35°C-70°C in 5°C Schritten   |
| <b>Timerfunktion</b>       | Individuell einstellbarer Timer von 1 – 72 Stunden in 60 min-Schritten  |
| <b>Standby-Verbrauch</b>   | <0,3 W  |
| <b>Geräuschpegel</b>       | 46 dBA  |
| <b>Tasten</b>              | 5 Tasten (TIME // TEMP // POWER ON/OFF // "+" // "-")   |
| <b>Displaytyp</b>          | LED-Display für Temperatur- und Restlaufzeitanzeige   |
| <b>Sicherheitsstandard</b> | Frontklappe mit Verriegelung und großem Sichtfenster  |
| <b>Eigenschaften</b>       | <ul style="list-style-type: none"> <li>• Umluftfunktion</li> <li>• 5 Einlegefächer mit insgesamt 2750 cm<sup>2</sup> Dörrfläche, spülmaschinengeeignet</li> <li>• je Fach zwei unterschiedliche Höhen einstellbar</li> <li>• An- und Ausschalter gut erreichbar auf der Front</li> <li>• kompakte Abmessungen, geringe Stellfläche</li> <li>• Antirutschfüße</li> </ul> |
| <b>Temperaturbereich</b>   | - 5° – 40°C   |